

**Torque Values****A4. Wheel Assembly Torque Values (Cont'd)**

Wheel Assembly	Bolt Torque		Material
	In-lb	N-M	Wheel
C-30174-1	95 D	10.7	(1)
C-30179	190-200 D	21.5-22.6	(1)
D-30204	95 D	10.7	(1)
D-30255	195 D	22.0	(1)
D-30260	195 D	22.0	(1)
D-30260-1	195 D	22.0	(1)
D-30291-1	195 D	22.0	A
D-30291-2	195 D	22.0	A
D-30291-3	195 D	22.0	A
D-30291-4	195 D	22.0	A
D-30291-5	195 D	22.0	A
D-30291-6	195 D	22.0	A
D-30380	95 D	10.7	A
C-30480	195 D	22.0	(1)
D-30500	145 D	16.4	A
D-30500-1	145 D	16.4	A

Wheel Assembly	Bolt Torque		Material
	In-lb	N-M	Wheel
D-30570	195 D	22.0	A
D-30580	195 D	22.0	(1)
D-30585	195 D	22.0	(1)
D-30660-1	145 D	16.4	A
D-30660-2	145 D	16.4	A
D-30660-3	145 D	16.4	A
D-30660-4	145 D	16.4	A
D-30660-5	145 D	16.4	A
D-30660-6	145 D	16.4	A
D-30660-7	145 D	16.4	A
D-30660-8	145 D	16.4	A
D-30660-9	145 D	16.4	A
D-30660-10	145 D	16.4	A
D-30665	145 D	16.4	A
D-30665-1	145 D	16.4	A

**A5. Tire Inflation Valve Stem Torques**

Dash No.	Inflation Valve P/N	Recommended Torque	
		In-Lb	N-M
-1	160-00700	50-60	5.7-6.8
-2	160-00900	165-200	18.7-22.6
-3	160-01100	75-100	8.4-11.3
-4	160-01200	35-45	4.0-5.1

Dash No.	Inflation Valve P/N	Recommended Torque	
		In-Lb	N-M
-5	160-01500	70-80	7.9-9.0
-6	160-01900	50-60	5.7-6.8
-7	160-02000	25-35	2.8-3.9